

Chain and sliding spray FLC 1010/1012 P

ELKALUB FLC 1010/1012 P is an oil spray without any solid lubricants based upon our EP lubricating concentrate ELKALUB LA 1. It is resistant to aging, chemically neutral, dirt dissolving, protects against corrosion, does not becomes resinous and displaces water from surfaces. After spraying on the parts to be lubricated, there remains only a very thin, transparent and adhesive film. The extremely creeping special lubricant guarantees, that the lubricating film is also forming in very narrow fits where it lubricates reliably. Slightly rusty or coked parts become mobile again and the loosening is supported. Although ELKALUB FLC 1010/1012 P creeps well into fits, the creeping ability on surfaces is minimal. This is of advantage e.g. for grippers and transport chains. ELKALUB FLC 1010/1012 P is available as a pump spray bottle (300 ml)
Request product Download data sheet

Base oil

mineral oil, ester oil

Operating temperature

-20 °C to 120 °C

Viscosity (active substance)

60 mm^2/s

Functionality

- corrosion protection
- universal lubricant
- creeping

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Suitable for

- slide bearing
- chains
- guides, curves

Packaging

- 300 ml pump spray

Industry

- printing industry
- drive technology
- furniture industry
- wood industry
- plant construction

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com