


**PFPE high-temperature grease GLS 595/N2**

KPFK2U-40
ELKALUB GLS 595/N2 is a high temperature grease mainly used for the lubrication of roller and slide bearings in the temperature range from -40 °C up to +250 °C. ELKALUB GLS 595/N2 is resistant to acids and alkalis as well as to organic solvents. Please note: ELKALUB GLS 595/N2 may not be mixed with other lubricants. Due to its high chemical stability ELKALUB GLS 595/N2 has been used for many years as nozzle sealing compound for adhesive machines at the end of the work process. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.
Request product Download data sheet

**Base oil**

PFPE

**Thickener**

solid lubricant

**Operating temperature**

-40 °C to 250 °C

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

**Viscosity Base oil**

360 mm²/s

**NLGI class**

- 2 | soft

**Functionality**

- food contact
- mounting devices

**Suitable for**

- roller bearing
- slide bearing
- assembly grease / fittings / o-rings
- valves

**Packaging**

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

**Industry**

- automotive
- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer
- plant construction

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com