

PTFE spray FLC 9025

ELKALUB FLC 9025 H1 PTFE spray is an Synthetic oil spray with PTFE. Excellent sliding lubrication properties, highest wear protection and emergency running properties thanks to solid lubricants. For guides, joints, shafts and bushings and other sliding elements. With H1 registration for use in the food and pharmaceutical industries.
Request product Download data sheet

Base oil

poly-alpha-olefin

Operating temperature

-40 °C to 160 °C

Viscosity (active substance)

58 mm²/s

Functionality

- corrosion protection
- lubricant / release agent
- universal lubricant
- food contact

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- creeping

Suitable for

- slide bearing
- guides, curves
- bed ways

Packaging

- 400 ml of aerosol

Industry

- food industry
- pharmaceutical and medical technology

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com