

Wheel hubs paste VP 910

KPF2U-20
ELKALUB VP 910 was developed for the lubrication of wheel hubs, rim flanks and centering rings. **ELKALUB VP 910** guarantees easy disassembly of wheel after long periods and stubborn winters.

Lubrication points:

[nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp] • Centering rings (material pairing: plastic-metal)
[nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp] • Rims support surface
[nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp] • Wheel hubs

Characteristics:

[nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp] • A high level of corrosion protection
[nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp] • Temperature Stable • Withstands splash water successfully
[nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp][nbsp] • High adherence

Application:
With the brush can, **ELKALUB VP 910** can be applied thinly and evenly to the surface to be lubricated.

Note:
The product must not be applied to the friction surfaces of the brake system! It is also not recommended to lubricate the thread of the wheel hub bolts. If rusty threads are cleaned when changing the wheel, we recommend our rust remover **ELKALUB FLC 1040**.

As a grease: Temperature range: -20 °C to 150 °C

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

As a separating paste: temperature range: -20°C to 1200 °C
Request product Download data sheet

Base oil

mineral oil

Thickener

inorganic, solid lubricant

Operating temperature

-20 °C to 1200 °C

Viscosity Base oil

460 mm²/s

NLGI class

- 1 | very soft
- 2 | soft

Functionality

- against tribocorrosion
- mounting devices

Packaging

- 200 ml brush can
- 1 kg can

Industry

- automotive
- plant construction

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com